

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
7 October 2004 (07.10.2004)


PCT

(10) International Publication Number  
**WO 2004/085898 A1**

- (51) International Patent Classification<sup>7</sup>: **F16L 1/20** **Kenyon** [GB/GB]; 2 Burnside Walk, Aboyne, Aberdeenshire AB34 5GJ (GB).
- (21) International Application Number: PCT/GB2004/001275 (74) Agent: FITZPATRICKS; 4 West Regent Street, Glasgow G2 1RS (GB).
- (22) International Filing Date: 23 March 2004 (23.03.2004) (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0306784.0 25 March 2003 (25.03.2003) GB
- (71) Applicant (for all designated States except US): STOLT OFFSHORE LIMITED [GB/GB]; Bucksburn House, Howes Road, Bucksburn, Aberdeen AB16 7QU (GB).
- (72) Inventor; and (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
- (75) Inventor/Applicant (for US only): WILLIS, Stewart,

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR LAYING OF ELONGATE ARTICLES FROM A VESSEL



(57) Abstract: This invention relates to apparatus and methods for laying of elongate articles from a vessel. The vessel includes a tower (2), on which is supported tensioning means (20,21), straightening means (19), and a hold-off clamp (14). The hold-off clamp (14) is mounted independently of the tower on a trolley (13) which can be moved into and out of alignment with the laying axis of the tower while supporting the elongate article under laying tension. This enables the pipe string to be moved out of the line of the tower (2) for the fitting of equipment such as mid-line connectors and PLETs. Methods are disclosed for using the apparatus for fitting a connection to the elongate article being laid using cranes etc provided on the vessel to move the trolley (13) and hold the laid pipe string or connection.



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*